



## Technical specification Cradles

	Unit	Model									
		6-12"	6-12" 7t	12-24"	24-36"	24-38"	30-42"	32-40"	36-48"	40-56"	48-60"
Application		Lift and lower a pipeline with a side boom									
<b>General</b>											
Pipe size	inch	6-12"	6-12"	12-24"	24-36"	24-38"	30-42"	32-40"	36-48"	40-56"	48-60"
Pipe size DN	mm	150-300	150-300	300-600	600-900	600-950	750-1050	800-1000	900-1200	1000-1400	1200-1500
Lifting capacity	t	4	7	14	27	27	38	38	38	44	49
Possible support frame		Side boom									
Ropes each Cradle	psc	2									
Wheels each Cradle	psc	24	24	20	24	20	28	28	28	32	32
Total weight	kg	145	170	750	1655	1690	2045	2040	2180	2480	2520
<b>Measurements and weight of traverse</b>											
Length	mm	622	622	1135	1490	1550	1700	1700	1850	2000	2180
Width	mm	620	650	950	1355	1355	1475	1475	1480	1480	1480
Height	mm	300	300	530	550	550	590	590	1000	1000	1000
Weight	kg	115	120	430	735	750	965	960	1100	1240	1280
<b>Measurements and weight of ropes</b>											
Length of one rope	mm	6230	6245	11350	11350	11350	14000	14000	14000	14700	14700
Total weight	kg	30	50	320	920	940	1080	1080	1080	1240	1240
<b>Article no.</b>		<b>40700</b>	<b>40700S</b>	<b>40701</b>	<b>40702</b>	<b>on request</b>	<b>on request</b>	<b>on request</b>	<b>40703</b>	<b>on request</b>	<b>40704</b>

Mistakes and changes are reserved